

TILIA T130

The Seisodin Tilia T130 is a highly integrated Strong Motion Accelerograph, tailored for precision structural and civil monitoring applications. The instruments provide ultra precise measurements using a state-of-the-art force-balance accelerometer (FBA) and 24-bit digitizers, all while being highly reliable and extremely easy to use.

The Tilia T130 comes with dual ethernet transceivers integrated directly in the instrument for up to 100m distance between daisy-chained devices. The integrated UPS in every instrument ensures continuous recording during power outages and cable breakages ensuring that data is never lost. The integrated ethernet transceivers support power-over-ethernet (PoE) enabling one instrument to provide power to the next one in the daisy chain, directly through the ethernet cable. This concept ensures highly cost-effective wiring. Tilia accelerographs rely on a hardware-backed phase-locked PTP integration, which ensures precise timing between instruments with industry-leading offsets between sensors as low as 40 nano-seconds!

Key Specifications

- 3 x Force-Balance Accelerometers
- ±4g, ±2g
- 155dB, 140dB @ 10Hz, 130dB @ 50Hz
- · 200Hz bandwidth
- 3 x 24-bit ADC's
- Daisy-chain topology
- 40ns timing precision
- Simultaneous Sampling
- Hardware backed PTP
- Power over Ethernet (PoE)
- Integrated UPS w. removable battery
- micro-SD + USB
- Optional Fiber optical transceivers built-in
- Optional MIL-spec connectors



2 x RJ45



2 x FIBER OPTIC



1 x RJ45 + 1 x FIBER OPTIC

Applications

Structural Health Monitoring

Dams, Highrise Buildings, Bridges, Tunnels, Railways, Monuments and historic buildings, Schools, Hospitals, Government buildings, Airports, Factories, Stadiums and sports fields



Contact us today
Seisodin ApS
Denmark
+45 93 83 87 09
www.seisodin.com
info@seisodin.com

