



TILIA T130F

The Seisodin Tilia T130F is a highly integrated Strong Motion Accelerograph with integrated dual fiber optical ethernet transceivers. The T130F is tailored for precision structural and civil monitoring applications. The instruments provide ultra precise measurements using 3 state-of-the-art force-balance accelerometers (FBA) and 24-bit digitizers.

The Tilia T130F comes with dual fiber optical ethernet transceivers integrated directly in the instrument for up to 2km or 20km (12mi) distance between daisy-chained devices. The integrated UPS in every instrument ensures continuous recording during power outages and cable breakages ensuring that data is never lost. Tilia accelerographs provide extremely precise timing. The system relies on a hardware-backed phase-locked PTP integration, which ensures industry-leading offsets between daisy chained devices as low as 40 nano-seconds!

The Tilia T130F is ideal for projects like dams, bridges, tunnels and railways where long distances between sensor nodes is required.

Key Specifications

- 3 x Force-Balance Accelerometers
- $\pm 4g, \pm 2g$
- 155dB, 140dB @ 10Hz, 130dB @ 50Hz
- 200Hz bandwidth
- 3 x 24-bit ADC's
- 2 x Built-in Fiber Optical Ethernet
- Up to 2 or 20km between instruments
- Daisy-chain topology
- 40ns timing precision
- Simultaneous Sampling
- Hardware backed PTP (IEEE 1588)
- Power over Ethernet (IEEE 802.3)
- Integrated UPS w. removable battery
- micro-SD + USB



2 x RJ45



2 x FIBER OPTIC



1 x RJ45 + 1 x FIBER OPTIC

Applications

Structural Health Monitoring

Dams, Highrise Buildings, Bridges, Tunnels, Railways, Monuments and historic buildings, Schools, Hospitals, Government buildings, Airports, Factories, Stadiums and sports fields



Contact us today
Seisodin ApS
Denmark
+45 93 83 87 09
www.seisodin.com
info@seisodin.com

